

**SPECIFICATION
FOR
SWITCHING POWER SUPPLY**

M/N: MPM-U653-DCF-B

Revision History

Version	Date	Change Items
Rev. 1.0	July.21. 2017	Established.



FEATURES

- ✓ 650W medical power supply with force air cooling. Peak power up to of 750W.
- ✓ Optional digital function to read PSU data by USB connector.
- ✓ Single + multi output versions up to 5 outputs included 5Vsb.
- ✓ IP to OP 2xMOPP; IP to Earth 1xMOPP.
- ✓ Thermally efficient U channel chassis design.
- ✓ Automatically fan speed control.
- ✓ Design to meet medical safety regulations.

Models & Ratings

Model Number	Wattage (Rated / Peak)	Output Voltage		Min. Current	Rated Current	Peak. Current
		V1	V2			
MPM-U653	650 W / 750 W	V1	+12 V	0 A	48 A	56.3 A
		V2	+5.1 Vsb	0 A	2A	----
		V3	-12V	0 A	0.2A	----
		V4	+5V	0 A	8A	
		V5	+3.3V	0 A	8A	

- Note:
1. Rated output is 650W with a built in fan model. In a open frame type with suffix "U" model name, it can be 450W(AC115V) at 50° C convection cooled environment.
 2. The peak output only at input voltage more than 100VAC, and max. 1000mS.
 3. See below Output Specification for detail test condition.
 4. Initial setting voltage is at input 115VAC and all outputs at 60% rated load.
 5. Total power is 650W.
 6. Model no. coding:

MPM-U653-X X X -X

1
2
3
4

- 1 : D or B means digital version or basic version
- 2 and 3 : optional DC/DC daughter board with U653 and U655 model only.
- 4 : A or B or C or D means different mechanical part. (see Mechanical Details)

Summary

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Input Range	85	115 / 230	264	VAC	Universal input range.
Input Frequency	47	50 / 60	63	Hz	AC input.
Efficiency		90	91	%	At input 230VAC, rated load, 1.0 hr. warm up.
Operation Temperature	-20		+70	°C	Derate linearly from 50°C, become 50% load at 70°C.
Weight		1650		g	
Dimensions	229 (L) x 127 (W) x 65 (H) mm, Tolerance +/- 0.5mm.				
EMC	EN 55011, EN 60601-1-2, EN 61000-3-2, EN 61000-3-3, IEC 61000-4-2, IEC 61000-4-3, IEC 61000-4-4, IEC 61000-4-5, IEC 61000-4-6, IEC 61000-4-8, IEC 61000-4-11				
Safety	IEC 60601-1, EN 60601-1, ANSI / AAMI ES60601-1:2005, CAN / CSA-C22.2 No. 60601-1:08				

Input

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Input Voltage	85	115 / 230	264	VAC	Universal input range.
Input Frequency	47	50 / 60	63	Hz	AC input.
Input Current	4		12.5	A	Nominal AC Input Voltage (115VAC/230VAC), rated load.
Inrush Current			30 / 60	A	Nominal AC Input Voltage (115VAC/230VAC), one cycle at 25°C cold start.
Patient Leakage Current		100/300		μA	Normal Condition / Single Fault Condition
Power Factor		0.92			Rated load @ 230 VAC
Input Protection	Dual non-user serviceable internally located AC input line fuse. Fuse : 15A / 250VAC * 2pcs				

Output

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Output Voltage		12 ^(V1)		VDC	
		5.1 ^(V2)			
		-12 ^(V3)			
		5 ^(V4)			
		3.3 ^(V5)			
Initial Set Accuracy		±1 ^(V1)		%	Initial setting accuracy is adjusted at input 115VAC and output at 60% rated load.
		±1 ^(V2)			
		±5 ^(V3)			
		±2 ^(V4)			
		±2 ^(V5)			
Minimum Load		0		A	
Start Up Delay		2 / 1.0		Sec.	Time required for initial output voltage stabilization. Nominal AC Input Voltage (115VAC/230VAC), rated load at 25°C.
Hold Up Time		16		mS	Nominal AC Input Voltage (115VAC/230VAC), rated load.
Line Regulation		±1 ^(V1) ±1 ^(V2) ±1 ^(V3) ±1 ^(V4) ±1 ^(V5)		%	Less than ±1% at rated load with ±10% changing in input voltage.
Load Regulation		±1 ^(V1) ±4 ^(V2) ±10 ^(V3) ±3 ^(V4) ±3 ^(V5)		%	Measured from 60% to 100% rated load and from 60% to 20% rated load (60% ±40% rated load).
Ripple & Noise		120 ^(V1) 100 ^(V2) 120 ^(V3) 50 ^(V4) 50 ^(V5)		mV	Measured at rated load by a 20MHz bandwidth limited oscilloscope and each output is connected with a 10μF Electrolytic Capacitor and a 0.1μF Ceramic Capacitor.
Overvoltage Protection	For some reason the power supply fails to control itself, the build-in over voltage protection circuit will shut down the outputs to prevent damaging external circuits.				
Overload Protection	Auto recovery.				
Short Circuit Protection	Fully protected against output overload and short circuit. Automatic recovery upon of overload condition.				
Remote On / Off	The power supply will be turned on when the power On/Off pin is connected to secondary GND.				
Remote Sense	N/A				


General

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Efficiency		90	91	%	At input 230VAC, rated load, 1.0 hr. warm up.
Isolation	IP to OP	4000		VAC	2 x MOPP
	IP to Ground	1500		VAC	1 x MOPP (Screw head to primary)
Switching Frequency		65		KHZ	
MTBF		148692		hrs.	MIL-HDBK-217F at 25°C
Power Good Signal (Only with -SB model)	When power is turned on, the power good signal will go high 100 mS to 500 mS after all output DC voltages are within regulation limits.				
Power Fail Signal (Only with -SB model)	The power fail signal will go low at least 1 mS before any of the output voltages fall below the regulation limits.				


Environmental

Characteristic	Minimum	Typical	Maximum	Units	Notes & Conditions
Low temperature start up	-20			°C	Some specification parameters maybe exceeded until after 20 minutes warm up period.
Operating Temperature	-20		+70	°C	Derate linearly above 50°C, performance curves will be provided after testing.
Storage Temperature	-40		+85	°C	
Relative Humidity	5		95	%RH	Non-condensing.
Operating Altitude		5000		m	
Vibration	0.26		6.09	G	Frequency Type: Sweep Frequency Frequency Range: 10~55 Hz Displacement: 1.0mm Sweep Rate: 60 minute / cycle Number of cycle: 1 cycle / axis Direction: X ,Y and Z axis

Derating curve



Main Output



5VSB

Performance curves of MPM-U653

EMC: Emissions

Phenomenon	Standard	Class	Notes & Conditions
Conducted	EN 55011 / CISPR 11 & FCC Part 18	B	1. Pass without enclosure. 2. Pass with or without a metal plate below the power supply.
Radiated	EN 55011 / CISPR 11 & FCC Part 18	B	
Harmonic Current	EN 61000-3-2	D	
Voltage Flicker	EN 61000-3-3		

- Note:
- Above specification is applied with output equal or below 650W. For higher output power, please re-confirm with us.
 - Above specification is based on the test conditions of EN 55011 / CISPR 11 & FCC Part 18. If there is any question when the power supply is applied to the system, please contact us for assistance.

EMC: Immunity

Phenomenon	Standard	Criteria	Notes & Conditions
ESD	IEC 61000-4-2	A	±15KV air discharge, ±8KV contact discharge
Radiated	IEC 61000-4-3	A	10V/m
EFT	IEC 61000-4-4	A	±2KV Line & PE, 100KHz
Surges	IEC 61000-4-5	A	L-N:±1KV, L/N-PE:±2KV
Conducted	IEC 61000-4-6	A	10V, 80% AM, 1KHz 150KHz~230MHz
Power Magnetic	IEC 61000-4-8	A	30A/m
Dips and Interruptions	IEC 61000-4-11	A A B B	DIP: >95%, 0.5 cycle DIP: 30%, 25 cycles (Note 2.) DIP: 60%, 5 cycles (Note 2.) INT: >95%, 250 cycles

Note:

- Above specification is applied with output equal or below 650W. For higher output power, please re-confirm with us.
- The test result of input 240Vac / 100Vac is criteria A / B.

Safety Approvals

Safety Agency	Safety Standard	Notes & Conditions
TUV	EN 60601-1: 2006+A11+A1+A12	Designed to meet (Medical 3.1 rd)
CB	IEC 60601-1: 2005+CORR. 1: 2006+CORR. 2: 2007+A1: 2012	
UL/cUL	ANSI/AAMI ES60601-1, CAN/CSA-C22. 2 No. 60601-1	Designed to meet (Medical 3.1 rd)

Digital Interface


Item	Content
Device class	Mini-USB Type B 12Mbps USB 2.0 Full-Speed, USB CDC class (RS232 Type)
CDC Baud rate	19200 bit/s
Protocol	Magic Power Standard protocol
Output Real-Time Item (Note 1)	Output Voltage Output Current Output Power Remote Signal PGPF Signal OTP Signal
Output Information Item (Note 1)	Model Name Firmware Version Rate Voltage Rate Power

Note:

- Customer can control the PSU ON / OFF and read above output data through the mini USB device with a PC.
- If any other control / read function is needed, please contact Magic Power to check the modification.

Mechanical Details

1. MPM-U653-XXX-A: With AC inlet, open frame type Estimated size 229 (L) x 127 (W) x 65 (H) mm.



Signal connector CN10	
Pin	Function
1	0V
2	+5VsB
3	PG/PF
4	Remove on/off


*Optional
Mates with Molex 70430-0143

Signal connector CN5			
Pin	Function	Pin	Function
1	+5V	6	0V
2	+5V	7	0V
3	+3.3V	8	0V
4	+3.3V	9	0V
5	-12V	10	0V

*Optional
Mates with Dinkle 0159-0310

Note: Optional daughter board for the digital function to read PSU data by mini USB type B connector and Magic Power software installed.

2. MPM-U653-XXX-B: With AC inlet, Fan and cover type Estimated size 229 (L) x 127 (W) x 65 (H) mm..



Signal connector CN10	
Pin	Function
1	0V
2	+5VsB
3	PG/PF
4	Remove on/off


*Optional
Mates with Molex 70430-0143

Signal connector CN5			
Pin	Function	Pin	Function
1	+5V	6	0V
2	+5V	7	0V
3	+3.3V	8	0V
4	+3.3V	9	0V
5	-12V	10	0V

*Optional
Mates with Dinkle 0159-0310

Note: Optional daughter board for the digital function to read PSU data by mini USB type B connector and Magic Power software installed.

3. MPM-U653-XXX-C: With input terminal block, open frame type, estimated size 229 (L) x 127 (W) x 65 (H) mm.



Signal connector CN10	
Pin	Function
1	0V
2	+5VsB
3	PG/PF
4	Remove on/off


*Optional
Mates with Molex 70430-0143

Signal connector CN5			
Pin	Function	Pin	Function
1	+5V	6	0V
2	+5V	7	0V
3	+3.3V	8	0V
4	+3.3V	9	0V
5	-12V	10	0V

*Optional
Mates with Dinkle 0159-0310

Note: Optional daughter board for the digital function to read PSU data by mini USB type B connector and Magic Power software installed.

4. MPM-U653-XXX-D: With input terminal block, fan and cover type, estimated size 229 (L) x 127 (W) x 65 (H) mm.



Signal connector CN10	
Pin	Function
1	0V
2	+5VsB
3	PG/PF
4	Remove on/off

*Optional
Mates with Molex 70430-0143






Signal connector CN5			
Pin	Function	Pin	Function
1	+5V	6	0V
2	+5V	7	0V
3	+3.3V	8	0V
4	+3.3V	9	0V
5	-12V	10	0V



*Optional
Mates with Dinkle 0159-0310

Note: Optional daughter board for the digital function to read PSU data by mini USB type B connector and Magic Power software installed.


Performance

(Input voltage: 115Vac)






EMI: EN55011 "B" (Conduction)




230Vac/rated load

EMI: FCC "B" (Conduction)




115Vac/rated load

EMI: EN55011 "B" (Radiation)



230Vac/rated load

EMI: FCC "B" (Radiation)



115Vac/rated load

Thermal Considerations

In order to ensure safe operation of the SPS in the end-use equipment, the temperature of the components listed in the table below must not be exceeded.

Temperature should be monitored using J type thermocouples placed on the hottest part of the component (out of any direct air flow). See mechanical details for component locations.

Temperature measurements at max. amb.	
Component	Max Temperature
T1	120°C
Q2	120°C
Q6,Q6A,Q7,Q7A	120°C
C3,C3A,C3B,C3C	105°C
C11,C11A,C11B,C11C,C11D,C11E	105°C